



FEATURES

- Brushless DC motor
- Integrated Soft start & MPPT
- Adjustable Speed & Timer Control
- All Stainless Steel
- High Efficiency

BENEFITS

- Lift up to 40m
- Flow rate up to 72,000 L/day
- Simple installation
- Maintenance-free
- High reliability & life expectancy

Bore part number: 4C1262200-B40 Dam Floating part number: 4C1262200-D40





TDH	L/MIN	L/DAY
10	200	72,000
20	160	57,600
30	120	43,200
40	90	32,400

SOLAR PUMP SYSTEM INCLUDES:



4CSS Pump, Motor, and Controller



40m of Power Cable low water probe & safety cabling



Heavy Duty Cyclone Rated Pole Mount Frame



8x370w Mono Crystalline Solar Panels



Bore Cap or Dam Float



Low water protection (bore kit only)

ACCESSORIES

6101 - Tank switch 6045NO - Pressure switch 6112 - 1.5" Double acting float valve 6016 - Sacrificial anode 1½"



Tank full switch inc 20m cable \$165+GST



Pressure Switch 12 bar inc gauge & fittings \$300+GST



Double acting float valve For use with Pressure Switch - \$300+GST



Anode \$120+GST



Shipping Dimensions
1x Crate 440 x 60 x 65cm @ 280kg
1x Pallet 200 x 115 x 45cm @ 190kg